
TEMPORARY TRAFFIC CONTROL TYPICAL APPLICATION IMPORTANT: THIS DRAWING SHALL BE USED IN COMBINATION WITH THE GENERAL NOTES AT THE BEGINNING OF 200 E STANDARDS NO. MD 104.00. **GAOR** ONE LANE NOTE: FLAGGER SHALL NEVER BE STATIONED MORE THAN 1000' AWAY FROM THE ADVANCE FLAGGER SIGN. KEY: CHANNELIZING DEVICES SIGN SUPPORT FACE OF SIGN ROAD WORK DIRECTION OF TRAFFIC (OPTIONAL) WORK SITE INTERVAL FLAGGER 10, 50° 100° ,008 BOAD WORK ONE LANE (OPTIONAL) ROAD 500 FT



Approval • Approval • Feberal Highway Administration

Approval • P-10-96 Approval • P-27-96 Revised Re

Maryland Department of Transportation STATE HIGHWAY ADMINISTRATION

STANDARDS FOR HIGHWAYS AND INCIDENTAL STRUCTURES FLAGGING OPERATION/2-LANE, 2-WAY EQL/LESS THAN 40 MPH/15 MIN - 12 HRS. OR DAYTIME USE

STANDARD NO.

MD 104.31-02